



产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JSB-56MP (1/2 晶体罩) 延时型式: 1 型		20.5×10.5×16 ≤13g	1Z	-55~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c.	349
JSB-56M (1 晶体罩) 延时型式: 1 型		20.5×10.5×22.5 ≤19g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c.	351
JSB-81M (1/5 晶体罩) 延时型式: 1、3、4、5 型		15.5×8.2×13.9 ≤7g	2Z	-55~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c. 0.5A, 115Va. c.	353
JSB-42M (1 晶体罩) 延时型式: 1 型		20.5×10.5×22.5 ≤19g		-55~125	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c.	355
JSB-54M (1 晶体罩) 延时型式: 3 型		20.5×10.5×22.5 ≤19g		-55~125	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c.	357
JSB-82M (1/2 晶体罩) 延时型式: 1、3、4、5 型		20.5×10.5×17.5 ≤15g		-55~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c.	359
JSB-55MP (1/2 晶体罩) 延时型式: 1 型		20.5×10.5×16 ≤13g		-55~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c.	361
JSB-55M (1 晶体罩) 延时型式: 1 型		20.5×10.5×22.5 ≤19g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c.	363
JSB-5MC (小型) 交流输入 延时型式: 1、3、4、5 型		32×22.4×47 ≤90g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c.	365
JSB-83M (小型) 延时型式: 1、3、4、5 型		26×13.5×32 ≤45g		-55~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c.	367

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JSB-86M (小型) 延时型式: 1、3、4、5型		26×26×32 ≤85g	3Z	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	25A, 28Vd. c. 10A, 115Va. c.	369
JSB-73M (小型) 两级延时 延时型式: 1型		26×26×28 ≤72g	4Z	-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c.	371
JSB-85M (小型) 延时型式: 1、3、4、5型		26×26×32 ≤85g		-55~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c.	373
➤ 延时型式: 2A、2B型; 负载电流: 2A≤I≤15A							
JSB-62M 2B 断电延时		29×25.4×50.8 ≤110g	1Z	-55~85	147m/s ² 10~2000Hz	3A, 28Vd. c.	376
JSB-62MA 2B 断电延时		29×25.4×50.8 ≤135g		-55~85	147m/s ² 10~2000Hz	10A, 28Vd. c.	378
JSB-76M (大功率型) 2A 释放延时		29×25.4×35 ≤80g		-55~85	147m/s ² 10~2000Hz	10A, 28Vd. c. 5A, 115Va. c.	380
JSB-63M (小型) 2B 断电延时		32×22.4×47 ≤110g	2Z	-55~85	147m/s ² 10~2000Hz	2A, 28Vd. c.	382
JSB-5MB (小型) 2B 断电延时		37×37×40 ≤160g		-55~85	196m/s ² 10~2000Hz	15A, 28Vd. c. 10A, 115Va. c.	384