


固体功率控制器选型目录

产品型号	产品照片	通道数	负载	通信方式	保护形式	外形尺寸 (mm) 及重量	工作温度 (℃)	页码
直流低压 (I 代分立型) 系列								
ZDSPS28M-05N-01-B		单通道	10~36Vd.c. 5A	无	I ² t	20.5×10.5×12.5 ≤10g	-55~85	
ZDSPS28M-05C-01		单通道	16~60Vd.c. 1~7A	CAN	I ² t	25.4×12.7×13.5 ≤12g	-55~85	
ZDSPS28M-10C-01		单通道	0~60Vd.c. 7~13A	CAN	I ² t	41×25×13.5 ≤40g	-55~85	
ZDSPS28M-15C-01		单通道	0~60Vd.c. 13~20A	CAN	I ² t	36×33×13.5 ≤45g	-55~85	
ZDSPS28M-30C		单通道	0~60Vd.c. 20~40A	CAN	I ² t	54.6×42.6×16 ≤125g	-55~85	
ZDSPS28M-50C		单通道	0~60Vd.c. 40~65A	CAN	I ² t	70.6×44.6×16 ≤155g	-55~85	
直流低压 (II 代集成型) 系列								
ZDSPC-028010M		单通道	0~60Vd.c. 1~10A	CAN/ 无	I ² t	20.5×10.5×11.5 ≤10g	-55~105	
ZDSPC-028015M		单通道	0~60Vd.c. 10~15A	CAN/ 无	I ² t	25×15×12.5 ≤15g	-55~105	

产品型号	产品照片	通道数	负载	通信方式	保护形式	外形尺寸（mm） 及重量	工作温度（℃）	页码
ZDSPC-028020M		单通道	0~60Vd.c. 15~20A	CAN	I ² t	26×26×13 ≤30g	-55~105	
ZDSPC-028040F		单通道	0~60Vd.c. 20~40A	CAN	I ² t	53×50×15 ≤70g	-55~105	
ZDSPC-028060F		单通道	0~60Vd.c. 40~60A	CAN	I ² t	61×50×15 ≤80g	-55~105	
直流低压（塑封型）系列								
ZDSPS28MD-05C-01		单通道	16~60Vd.c. 1~5A	CAN	I ² t	25.4×12.7×13.5 ≤12g	-55~85	
ZDSPS28MD-10C-01		单通道	0~60Vd.c. 5~10A	CAN	I ² t	41×26×13.5 ≤30g	-55~85	
ZDSPS28MD-15C-01		单通道	0~60Vd.c. 10~15A	CAN	I ² t	36×33×13.5 ≤40g	-55~85	
ZDSPS28MD-30C		单通道	0~60Vd.c. 15~30A	CAN	I ² t	83×50×20 ≤160g	-55~85	
ZDSPS28MD-50C		单通道	0~60Vd.c. 30~50A	CAN	I ² t	95×50×20 ≤180g	-55~85	

产品型号	产品照片	通道数	负载	通信方式	保护形式	外形尺寸 (mm) 及重量	工作温度 (℃)	页码
直流低压 (点保护) 系列								
ZDSPS28M1-11		单通道	16~60Vd.c. 1A	无	点保护 2.5A	26×16×9.7 ≤15g	-55~85	
ZDSPS28M1-21		单通道	16~60Vd.c. 2A	无	点保护 2.5A	20.5×10.5×10.5 ≤15g	-55~85	
ZDSPC28M-1G6-01-A		单通道	0~60Vd.c. 1.6A	无	点保护 3.2A	21×15×13.5 ≤15g	-55~85	
ZDSPC28M-3G0-01-A		单通道	22~30Vd.c. 3A	无	点保护 7A	28.5×16×12 ≤20g	-55~85	
ZDSPS28M-05N-01-A		单通道	12~32Vd.c. 5A	无	点保护 7A	25.2×12.7×13.5 ≤12g	-55~85	
ZDSPS28M-05C-01-A		单通道	16~60Vd.c. 5A	CAN	点保护 9A	25.4×12.7×13.5 ≤12g	-55~85	
ZDSPC28M-7G3-01-A		单通道	0~60Vd.c. 7.3A	无	点保护 14.6A	30×22×13.5 ≤30g	-55~85	
ZDSPC28M-8G9-01-A		单通道	0~60Vd.c. 8.9A	无	点保护 17.8A	30×22×13.5 ≤30g	-55~85	

产品型号	产品照片	通道数	负载	通信方式	保护形式	外形尺寸 (mm) 及重量	工作温度 (℃)	页码
直流高压系列								
ZDSPS270M-05C-01		单通道	250~360Vd. c. 1~7A	CAN	I ² t	36×33×14.5 ≤45g	-55~85	
ZDSPS270M-15C-01		单通道	250~360Vd. c. 7~15A	CAN	I ² t	54.6×42.6×14.5 ≤90g	-55~85	
ZDSPS270M-20C-01		单通道	250~360Vd. c. 15~25A	CAN	I ² t	54.6×61.1×14.5 ≤130g	-55~85	
ZDSPC-540010F		单通道	360~550Vd. c. 5~10A	CAN	I ² t	67×45×20 ≤150g	-55~100	
ZDSPC4H-270048F		四通道	0~360Vd. c. 7~12A	CAN	I ² t	90×57×15 ≤120g	-55~105	
交流系列								
ZASPC-115005F		单通道	90~132Va. c. 1~5A	CAN	I ² t	40×40×18 ≤55g	-55~100	
ZASPC-115015F		单通道	90~132Va. c. 3~15A	CAN	I ² t	64×61×12.7 ≤130g	-55~100	
ZASPC-220005F		单通道	180~250Va. c. 1~5A	CAN	I ² t	40×40×18 ≤80g	-55~100	