




二、固体继电器

类别	输出 电流 (A)	输出电压 (V)	产品型号	产品照片	外形尺寸 (mm)	工作温度 (°C)	页 码
一组转换	±0.20	±35	JGW-QY34M		8.6x8.6x7.3	-55~105	136
	3	50	JGC-QY45M		15.5x8.2x7.5	-55~105	139
一组常开 (低压)	2	60	JGC-433M		10.5x10.5x7.5	-55~105	141
	5	60	JGC-1001M		25x15x10.5	-55~105	144
	5	50	JGC-1H50DC5M		20.5x10.5x10.5	-55~105	147
	5	120	JGX-QY3MD		22x14x7.5	-55~105	150
	10	60	JGC-1001MA		25x15x10.5	-55~105	153
	10	90	JGC-QY24M		25x15x10.5	-55~105	156
	10	100	JGX-QY5M		30x20x7.5	-55~105	159
	±12.5	±60	JGC-QY41M		21.2x21.2x10.6	-55~105	161



类别	输出 电流 (A)	输出电压 (V)	产品型号	产品照片	外形尺寸 (mm)	工作温度 (°C)	页 码
一组常开 (低压)	15	80	JGX-QY3MB		22x14x7.5	-55~105	163
	20	60	JGX-QY3M		31.9x22.3x12	-55~105	166
	20	60	JGX-QY3MA		22x14x7.5	-55~105	169
	25	50	JG-26M		56x34x10.4	-55~85	172
	25	80	JGX-28MB		45x34x10.4	-55~105	174
	40	80	JG-58MA		56x34x10	-55~105	176
	100	80	JGX-1H80DC100M		45.6x34.7x12	-55~105	179
一组常开 (高压)	0.1	750	JGX-QY8M		32x22.5x14	-55~105	181
	5	450	JGX-QY16M		30x20x12.5	-55~105	183
	12.5	540	JGC-QY44M		22x17x10	-55~105	186
	50	270	JGX-5211M		62.5x66x21.5	-55~105	188
一组常开 (双向)	±5/10	90	JGC-0516MZ		21.8x12.8x10	-55~105	190



类别	输出 电流 (A)	输出电压 (V)	产品型号	产品照片	外形尺寸 (mm)	工作温度 (°C)	页 码
一组常开 (双向)	±15	±80	JGX-QY42M		30x20x12.5	-55~105	192
一组常开 (交流)	1/2/5	250	JGX-QY6M		30x20x12.5	-55~105	194
一组常闭 (高压)	0.1	750	JGX-QY9M		32x22.5x14	-55~105	196
两组 常开	±1	±28	JRC-5M		φ 13x14	-55~105	198
	5	50	2DHMK40-1		25x15x10.5	-55~105	200
四组 常开	±1	±50	JGC-17MB		24x22x11.5	-55~105	202
	±1	±55	JGX-5073M		26x26x16	-55~85	204
	3	27	JGC-17MA		24x22x11.5	-55~85	206
	4	60	JGC-17M		24x22x11.5	-55~105	208
	4	60	JGC-17MD		24x22x11.5	-55~85	210
	7	50	JGX-36MA		41.5x23.8x10.6	-55~105	212



类别	输出 电流 (mA)	输出 电压 (V)	产品型号	产品照片	外形尺寸 (mm)	工作温度 (°C)	页码
四组 常开	7	80	JGX-4H50DC7M		41.5x23.8x10.6	-55~105	214
八路 常开	4	60	GKM-QY5M		23.6x23.6x10.2	-55~105	216
电机 正反转	20	60	JGX-5255MA		44x34x20	-55~105	218

三、固体延时

类别	输出 电流 (mA)	输出 电压 (V)	产品型号	产品照片	外形尺寸 (mm)	工作温度 (°C)	页码
固体 延时模块	5	14	JSB-807M		20.5x10.5x11.5	-55~105	221
	30	18	JSB-800M		18.9x8.0x7.9	-55~105	223
固体 延时继电器	100	32	JSB-810M		15.5x8.2x8.2	-55~85	225
	2000	80	JSB-809M		20.5x11.5x11.5	-55~105	227

四、浪涌电流抑制器

类别	输出 电流 (A)	输出 电压 (V)	产品型号	产品照片	外形尺寸 (mm)	工作温度 (°C)	页码
直流 (单路)	5	28	QYH-2M		31.9x22.3x12	-55~105	230