






产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (℃)	振 动	触点负载	页码
JMW-270M (T0-5) 贯军标		$\phi 8.51 \times 7.11$ $\leq 2.84g$	2Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	1A, 28Vd. c. 失效率等级: L 级或 M 级	45
JMW-270M (T0-5) 增加接地 引脚		$\phi 8.51 \times 7.11$ $\leq 1.8g$		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	1A, 28Vd. c. 失效率等级: M 级	47
JMW-271M (T0-5) 贯军标		$\phi 8.51 \times 7.11$ $\leq 2.9g$		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	1A, 28Vd. c. 失效率等级: L 级	49
JMW-270MA JMW-271MA (T0-5)		$\phi 8.51 \times 7.11$ $\leq 2.9g$		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	1A, 28Vd. c.	51
➤ T0-5 射频继电器, 负载频率 (0~5) GHz							
JPW-220M (T0-5)		8.51×8.51×7.37 $\leq 2.55g$	2Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	(0~5) GHz	53

二、 晶体罩及功率继电器

➤ 负载电流: $I \leq 1A$

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JRC-6MA (超小型)		$10.8 \times 5.9 \times 15.3$ $\leq 3.4g$	1Z	-55~125	正弦: $147m/s^2$ 10~2000Hz 随机: $20 (m/s^2)^2/Hz$	1A, 30Vd. c.	57
JRC-098M (超小型)		$10.4 \times 5.3 \times 10.8$ $\leq 3.0g$	2Z	-65~125	正弦: $294m/s^2$ 10~3000Hz 随机: $30 (m/s^2)^2/Hz$	1A, 28Vd. c.	59

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (℃)	振 动	触点负载	页码
KJRC-220M (1/6 晶体罩) 贯军标		13×6×11 ≤4.3g	2Z	-65~125	正弦: 196m/s ² 10~2000Hz 随机: 40 (m/s ²) ² /Hz	1A, 28Vd. c. 失效率等级:L 级	61
JRC-220M (1/6 晶体罩)		13×6×11 ≤4.0g		-65~125	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	1A, 28Vd. c.	63
➤ 负载电流: 1A<I≤5A							
KJRC-200M JRC-201M (1/5 晶体罩) 贯军标		15.5×8.2×8.2 ≤4.9g	2Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	2A, 28Vd. c. 0.5A, 115Va. c. 失效率等级: L 级	65
JRC-200MA JRC-201MA JRC-202MA (1/5 晶体罩)		15.5×8.2×8.2 ≤5.0g		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c. 0.5A, 115Va. c.	67
JRC-023M (1/2 晶体罩)		20.5×10.5×11.5 ≤11g		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c.	70
KJZC-4M (1/2 晶体罩) 贯军标		20.5×10.5×10.5 ≤10g		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	2A, 28Vd. c. 失效率等级: M 级	72
JZC-4M (1/2 晶体罩)		20.5×10.5×11.5 ≤11g		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c.	74
KJZC-4MH (1/2 晶体罩) 贯军标		20.5×10.5×11.5 ≤11g		-65~105	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c. 失效率等级:L 级	76
JZC-4MH (1/2 晶体罩)		20.5×10.5×11.5 ≤11g		-65~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	5A, 28Vd. c. 2A, 115Va. c.	78

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (℃)	振 动	触点负载	页码
JRC-071M (1/2 晶体罩) 贯军标		20.5×10.5×11.5 ≤12g	4Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 30 (m/s ²) ² /Hz	2A, 28Vd. c. 失效率等级:M 级	80
JRC-071M (1/2 晶体罩)		20.5×10.5×11.5 ≤12g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c.	82
JZC-6Z2CM (1/2 晶体罩)		20.5×10.5×11.5 ≤12g	6Z	-65~125	正弦: 196m/s ² 10~2000Hz 随机: 30 (m/s ²) ² /Hz	2A, 28Vd. c. 失效率等级:L 级	84
KJRC-9MT (1 晶体罩) 贯军标		21×11×25 ≤22g		-65~125	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	2A, 28Vd. c. 1A, 28Vd. c. 失效率等级:L 级	86
JRC-9MT (1 晶体罩)		21×11×25 ≤22g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	2A, 28Vd. c.	88
➤ 负载电流: 5A<I≤20A							
KJZC-102M (1/2 晶体罩) 贯军标		20.5×10.5×11.5 ≤11g	1Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c. 失效率等级:L 级	90
JZC-102M (1/2 晶体罩)		20.5×10.5×11.5 ≤11g		-65~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c. 3A, 220Va. c.	92
JZC-102MH (1/2 晶体罩)		20.5×10.5×11.5 ≤13g		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	15A, 28Vd. c.	94
JZC-4MT (1/2 晶体罩)		20.5×10.5×11.5 ≤13g	2Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c.	96

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JZC-4MB (1/2 晶体罩)		20.5×10.5×11.5 ≤13g	2Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	10A, 28Vd. c. 35A, 100ms, 28Vd. c.	98
JQX-20M (1/2立方英寸) 贯军标		26×13.5×26 ≤45g		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	10A, 28Vd. c. 10A, 115Va. c. 失效率等级: L级	100
JQX-20M (1/2立方英寸)		26×13.5×26 ≤45g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 5A, 115Va. c. 3A, 220Va. c.	102
JQX-2Z15BM (1/2立方英寸)		26×13×26 ≤45g		-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	15A, 28Vd. c. 失效率等级: M级	104
JQX-3MH (小型)		37.5×26×45 ≤160g		-60~85	正弦: 147m/s ² 10~2000Hz 随机: 0.1g ² /Hz	10A, 60Vd. c. 10A, 220Va. c.	106
JZX-16M (小型)		32×18×32 ≤65g	4Z	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	10A, 28Vd. c. 10A, 115Va. c.	108
JQX-40M (1立方英寸)		26×26×26 ≤77g		-55~85	正弦: 196m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	10A, 28Vd. c. 10A, 115Va. c.	110
JQX-3M (小型)		37.5×26×45 ≤150g		-55~85	正弦: 98m/s ² 10~2000Hz 随机: 6 (m/s ²) ² /Hz	15A, 28Vd. c. 15A, 115Va. c.	112
JQX-008M (小型)		37.5×26×45 ≤150g	6Z	-55~85	正弦: 98m/s ² 10~2000Hz 随机: 6 (m/s ²) ² /Hz	10A, 28Vd. c. 10A, 115Va. c.	114
➤ 负载电流: 20A<I≤50A							

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JQX-QY2M (1/2立方英寸)		26×13.5×26 ≤45g	1Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	25A, 28Vd. c. 25A, 115Va. c.	116
JQX-3MX (小型)		37.5×26×43 ≤160g		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	50A, 28Vd. c. 50A, 115Va. c.	118
JQX-6MC (小型)		32×18×32 ≤65g	1H	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	50A, 28Vd. c. 30A, 115Va. c. 20A, 220Va. c.	120
JQX-6MS (小型)		32×18×32 ≤65g		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	25A, 60Vd. c. 25A, 115Va. c. 15A, 220Va. c.	122
JQX-6MB (小型)		32×18×32 ≤65g	2H	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	30A, 28Vd. c. 20A, 115Va. c. 10A, 220Va. c.	124
JQX-3MC (小型) 贯军标		37.5×26×45 ≤150g		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	40A, 28Vd. c. 30A, 40Vd. c. 40A, 115Va. c.	126
JQX-3MC (小型)		37.5×26×45 ≤150g		-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	40A, 28Vd. c. 30A, 40Vd. c. 40A, 115Va. c. 10A, 220Va. c.	128
JQX-6MT (小型)		32×18×32 ≤65g	2Z	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 20 (m/s ²) ² /Hz	30A, 28Vd. c. 15A, 115Va. c. 10A, 220Va. c.	130
JQX-3Z25BM (1立方英寸)		26×26×26 ≤45g	3Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	25A, 28Vd. c. 失效率等级: L 级	132
KJQX-3MJ (小型) 贯军标		37.5×26×45 ≤150g	3D	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	30A, 28Vd. c. 15A, 115Va. c.	134

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JQX-3MJ (小型)		37.5×26×45 ≤150g	3D	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	30A, 28Vd. c. 15A, 115Va. c.	136
JQX-3MD (小型)		37.5×26×45 ≤150g	4H	-55~85	正弦: 147m/s ² 10~2000Hz 随机: 10 (m/s ²) ² /Hz	30A, 28Vd. c. 15A, 115Va. c 10A, 220Va. c.	138