

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
<b>单相接触器</b>							
JQ-81F		38×26×47 ≤125g	1H	-60~85	正弦: 98m/s <sup>2</sup> 10~200Hz	25A, 28Vd. c.	158
JQ-42F		60×38.5×54 ≤200g		-60~85	正弦: 98m/s <sup>2</sup> 5~200Hz	50A, 48Vd. c. 25A, 220Va. c.	160
JQ-41F		71×43×68 ≤320g		-60~85	正弦: 98m/s <sup>2</sup> 5~200Hz	100A, 48Vd. c. 50A, 220Va. c.	162
JQ-40F		85×57×85 ≤550g		-60~85	正弦: 98m/s <sup>2</sup> 5~200Hz	200A, 48Vd. c. 100A, 220Va. c.	164
JQ-39F		104.5×65×108 ≤1000g		-60~85	正弦: 98m/s <sup>2</sup> 5~200Hz	400A, 48Vd. c. 200A, 220Va. c.	166
JQ-56F		131×80×125 ≤1650g		-60~85	正弦: 98m/s <sup>2</sup> 5~200Hz	600A, 28Vd. c. 300A, 220Va. c.	168
JQ-200D		85×57×86.5 ≤550g		1D	-60~85	正弦: 98m/s <sup>2</sup> 5~500Hz	200A, 48Vd. c. 100A, 220Va. c.
JQ-400D		105×65×104.5 ≤1000g	-60~85		正弦: 98m/s <sup>2</sup> 5~500Hz	400A, 48Vd. c. 200A, 220Va. c.	172

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JQ-48F		62×48×36 ≤168g	1H	-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz 随机: 0.07g <sup>2</sup> /Hz	80A, 28Vd. c. 40A, 220Va. c.	174
JQ-91F		78.5×48×35.7 ≤241g		-55~85	正弦: 98m/s <sup>2</sup> 10~2000Hz 随机: 0.04g <sup>2</sup> /Hz	主: 100A, 28.5Vd. c. 辅: 5A, 28Vd. c.	176
JQ-34F		68×48×39.5 ≤230g		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz 随机: 0.07g <sup>2</sup> /Hz	125A, 28Vd. c. 60A, 220Va. c.	178
JQ-35F		95×65×42.5 ≤420g		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz 随机: 0.07g <sup>2</sup> /Hz	主: 200A, 28Vd. c. 100A, 220Va. c. 辅: 5A, 28Vd. c.	180
JQ-35FH		96×65×42.5 ≤380g		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz 随机: 0.07g <sup>2</sup> /Hz	200A, 28Vd. c. 100A, 220Va. c.	182
JQ-52F		96×65×42.5 ≤420g		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz 随机: 0.07g <sup>2</sup> /Hz	主: 320A, 28Vd. c. 辅: 5A, 28Vd. c.	184
JQ-52FH		96×65×42.5 ≤420g		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz 随机: 0.07g <sup>2</sup> /Hz	320A, 28Vd. c.	186
JQ-49F		121×70×62.5 880g±10%		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz	主: 500A, 28Vd. c. 辅: 5A, 28Vd. c.	188
JQ-49FH		121×70×62.5 880g±10%		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz	500A, 28Vd. c.	190
单相密封接触器							

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JQ-61M		80×55×50 ≤600g	1H	-55~85	正弦: 98m/s <sup>2</sup> 5~500Hz	200A, 28Vd. c. 100A, 220Va. c.	192
JQ-30M		93×89×75 ≤800g		-55~85	正弦: 98m/s <sup>2</sup> 5~2000Hz	主: 400A, 28Vd. c. 辅: 5A, 28Vd. c.	194