

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (℃)	振 动	触点负载	页码
三相密封接触器							
JCQ-3H120M		87.5×87.5×85 ≤910g	3H	-55~85	随机振动: 0.084 g ² /Hz, 20~2000 Hz	主: 120A, 115Va. c. 电机: 80A, 115Va. c. 辅: 5A, 28Vd. c.	233
JCQ-3Z60M		61×61×79 ≤460g	3Z	-55~85	随机振动: 0.084 g ² /Hz, 10~2000 Hz	主: 60A, 115Va. c. 电机: 40A, 115Va. c. 辅: 5A, 28Vd. c.	235
JCQ-3Z90M		91×86×86.4 ≤820g		-55~85	随机振动: 0.05 g ² /Hz, 5~2000 Hz	主: 90A, 115Va. c. 电机: 80A, 115Va. c. 辅: 5A, 28Vd. c.	237
JCQ-3Z120M		87.5×87.5×104 ≤1030g		-55~85	随机振动: 0.084 g ² /Hz, 20~2000 Hz	主: 120A, 115Va. c. 电机: 80A, 115Va. c. 辅: 5A, 28Vd. c.	239
JQ-50M		118.5×91.5×104 ≤1200g		-55~85	随机振动: 0.084 g ² /Hz, 20~2000 Hz	主: 175A, 115Va. c. 电机: 80A, 115Va. c. 辅: 5A, 28Vd. c.	241
BUSBAR接触器							
JQ-QY34F		80×35.5×70 ≤196g	1H	-55~85	见内页振动频谱 图	主: 100A, 28Vd. c. 辅: 5A, 28Vd. c.	243
JQ-QY35F		87.5×35.5×74 ≤277g		-55~85	见内页振动频谱 图	主: 200A, 28Vd. c. 辅: 5A, 28Vd. c.	247
JQ-80F		94×35.5×78 ≤350g		-55~85	见内页振动频谱 图	主: 400A, 28Vd. c. 辅: 5A, 28Vd. c.	251
JQ-QY42F		97×42×95 ≤550g		-55~85	见内页振动频谱 图	主: 600A, 28Vd. c. 辅: 5A, 28Vd. c.	256

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JQ-QY45F		87.5×35.5×74 ≤300g	1D	-55~85	见内页振动频谱 图	主: 200A, 28Vd. c. 辅: 5A, 28Vd. c.	259
JCQ-1D400F		94×35.5×80 ≤350g		-55~85	见内页振动频谱 图	主: 400A, 28Vd. c. 辅: 5A, 28Vd. c.	263
JCQ-1D1H400F		91×91×101.5 ≤500g	1D1H	-55~85	见内页振动频谱 图	主: 400A, 28Vd. c. 辅: 5A, 28Vd. c.	266
JQ-83F		60×58×81 ≤320g	3H	-55~85	见内页振动频谱 图	主: 90A, 115Va. c. 辅: 5A, 28Vd. c.	269
JQ-QY33F		66×89×90 ≤585g		-55~85	见内页振动频谱 图	主: 175A, 115Va. c. 辅: 5A, 28Vd. c.	274
JQ-85F		93.5×74×110 ≤822g		-55~85	见内页振动频谱 图	主: 275A, 115Va. c. 辅: 5A, 28Vd. c.	279
JQ-QY17F		93.5×109×114 ≤1390g		-55~85	见内页振动频谱 图	主: 350A, 115Va. c. 辅: 5A, 28Vd. c.	284
JCQ-3H450F		107×102×117.4 ≤1470g		-55~85	见内页振动频谱 图	主: 425A, 115Va. c. 304A, 230Va. c. 辅: 5A, 28Vd. c.	288