

浪涌抑制模块选型目录

产品名称	产品型号	产品照片	输入电压 (V)	额定工作 电流(A)	限流保护 门限值(A)	外形尺寸(mm) 及重量	工作温度 (℃)	页 码
电压浪涌 抑制模块	QSM1-2801-V INH281M-1		8~32	1	无	16×16×7.5 ≤10g	-55~105	
	QSM1-2801P-V INH281M-1P		8~32	1	2	16×16×7.5 ≤10g	-55~105	
	QSM1-2802-V INH281M-2		8~32	2	无	26×16×10.5 ≤15g	-55~105	
	QSM1-2802P-V INH281M-2P		8~32	2	4	26×16×10.5 ≤15g	-55~105	
	QSM1-2803-VL INH281M-3		8~32	3	无	21×21×10.5 ≤15g	-55~105	
	QSM1-2803P-V INH281M-3P		8~32	3	5	21×21×10.5 ≤15g	-55~105	
	QSM1-2805-VM		8~32	5	无	26×16×10.5 ≤15g	-55~105	
	QSM1-2805-VL INH281M-5		8~32	5	无	30×27.4×13 ≤25g	-55~105	
	QSM1-2805P-V INH281M-5P		8~32	5	10	30×27.4×13 ≤25g	-55~105	
浪涌电流 抑制模块	QYH-2M		28	5	25	31.9×22.3×12 ≤50g	-55~105	
	QYH-1M		50	20	100	44×34×20 ≤100g	-55~105	

注：QSM1 系列及 INH281M 系列对应产品仅型号不同，性能指标一致。