

➤ 磁保持继电器，负载电流：5A~15A

JMC-153M (1/2 晶体罩)		21×11×11 ≤12g	2Z	-65~125	正弦： 294m/s ² 10~3000Hz 随机： 40 (m/s ²) ² /Hz	5A, 28Vd. c. 失效率等级: L 级	140
JMC-2Z5CM (1/2 晶体罩)		21×11×11.5 ≤11g		-65~125	正弦： 294m/s ² 10~3000Hz 随机： 40 (m/s ²) ² /Hz	5A, 28Vd. c. 失效率等级: M 级	142
JMC-2Z5BM (1/5 立方英寸)		20.6×10.5×16.3 ≤18g		-65~125	正弦： 294m/s ² 10~3000Hz 随机： 40 (m/s ²) ² /Hz	5A, 28Vd. c. 失效率等级: M 级	144
JMX-2015MH (小型)		25×15×27.5 ≤50g		-65~125	正弦： 294m/s ² 10~3000Hz 随机： 0.4g ² /Hz	15A, 28Vd. c. 5A, 45Vd. c. 15A, 115Va. c.	146
JMX-2015MJ (小型)		25×15×27.5 ≤50g		-65~125	正弦： 294m/s ² 10~3000Hz 随机： 0.4g ² /Hz	15A, 28Vd. c. 5A, 45Vd. c. 15A, 115Va. c.	148
JMX-2H10BM (1 立方英尺)		26×26×26 ≤75g	2H	-65~125	正弦： 196m/s ² 10~2000Hz 随机： 20 (m/s ²) ² /Hz	10A, 110Vd. c	150
JMC-4Z5BM (2/5立方英寸)		20.6×20.6×16.3 ≤30g	4Z	-65~125	正弦： 294m/s ² 10~3000Hz 随机： 40 (m/s ²) ² /Hz	5A, 28Vd. c 失效率等级: L 级	152

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JMX-4Z15BM (1 立方英尺)		26×26×26 ≤65g	4Z	-65~125	正弦: 294m/s ² 10~3000Hz 随机: 40 (m/s ²) ² /Hz	15A, 28Vd.c 失效率等级: L 级	154