

产品型号	产品照片	外形尺寸(mm) 及重量	触点 型式	环境温度 (°C)	振 动	触点负载	页码
JCQ-1H200HFA		95×47×89 ≤600g	1H	-55~85	正弦振动: 98 m/s ² , 10~2000 Hz 随机振动: 见内页图谱	主: 200A, 750Vd. c. 200A, 1000Vd. c. 辅: 5A, 28Vd. c.	309
JCQ-1H400HF		114×66×94 ≤1250g		-55~85	正弦振动: 39.2 m/s ² , 10~2000 Hz 随机振动: 0.04 g ² /Hz, 10~2000 Hz	主: 400A, 750Vd. c. 辅: 5A, 24Vd. c.	311
JCQ-1H600HFB		75×75×112 ≤850g		-55~85	正弦振动: 147 m/s ² , 10~2000 Hz 随机振动: 见内页图谱	主: 600A, 270Vd. c. 600A, 540Vd. c. 600A, 750Vd. c. 辅: 5A, 28Vd. c.	313
JQ-QY25F		60×60×60 ≤500g		-55~85	正弦: 98m/s ² 10~2000Hz	100A, 270Vd. c. 200A, 270Vd. c. 300A, 270Vd. c. 300A, 750Vd. c.	315
JQ-QY5F		60×60×60 ≤500g	1D	-55~85	正弦: 98m/s ² 10~2000Hz	100A, 270Vd. c. 200A, 270Vd. c. 300A, 270Vd. c. 100A, 750Vd. c.	317
磁保持高压直流接触器							
JQ-QY10F		60×60×41 ≤300g	1H	-55~85	正弦振动: 294 m/s ² , 10~2000 Hz 随机振动: 0.4 g ² /Hz, 10~2000Hz	100A, 120Vd. c.	319
JQ-QY9F		75×75×55 ≤550g		-55~85	正弦振动: 294 m/s ² , 10~2000 Hz 随机振动: 0.4 g ² /Hz, 10~2000Hz	200A, 120Vd. c.	321
JQ-QY50F		60×60×41 ≤300g		-55~85	正弦振动: 294 m/s ² , 10~2000 Hz 随机振动: 0.4 g ² /Hz, 10~2000Hz	50 A, 270 Vd. c. 100 A, 270Vd. c.	323
JQ-QY49F		75×75×55 ≤550g		-55~85	正弦振动: 294 m/s ² , 10~2000 Hz 随机振动: 0.4 g ² /Hz, 10~2000Hz	150 A, 270Vd. c. 200 A, 270Vd. c.	325