

四、电磁锁控装置

产品型号	产品照片	外形尺寸(mm) 及重量	工作温度 (°C)	拔销力/ 扭矩	行程 (mm)	类别	页码
DCT-T1.7		$\Phi 15 \times 20$ $\leq 40g$	-55~85	$\geq 7.5N$	$\geq 1.7mm$	直动式	329
DCT-T02		$\Phi 12 \times 20$ $\leq 20g$	-55~85	$\geq 10N$	$\geq 2mm$	直动式	331
DCT-T2.5		$\Phi 16.9 \times 30.9$ $\leq 45g$	-55~85	$\geq 10N$	$\geq 2.5mm$	直动式	333
J/DF44-DCT		$39 \times 39 \times 80$ $\leq 850g$	-55~60	$\geq 50N$	$\geq 4mm$	直动式	335
DCT-T1.5		$\Phi 36 \times 36$ $\leq 260g$	-40~70	$\geq 200N$	1.5~1.6mm	高速电磁铁	337
DCT-T02B		$\Phi 52 \times 64$ $\leq 900g$	-40~70	$\geq 300N$	2.0~2.2mm	高速电磁铁	339
DCT-R11		$47 \times 47 \times 30$ $\leq 320g$	-55~85	$20N \cdot cm$	$11^\circ \sim 12.7^\circ$	旋转式	341
DCT-R11A		$50 \times 50 \times 30$ $\leq 340g$	-55~85	$20N \cdot cm$	$11^\circ \sim 12.7^\circ$	旋转式	343